

# REMI

**PLUS**  
Performance  
Leading Technology  
User Friendly  
Safety

## Cold Cabinets



The REMI Cold Cabinets are designed for bio sample storage applications in pharmaceutical, microbiology, biotechnology, chemical & research labs.

**These cabinets are available in standard & GMP versions.**

### Performance

- Temperature range 2°C to 12°C
- Powerful fan motor for forced air circulation to maintain uniform conditions inside chamber
- Validation protocol with IQ, OQ, DQ Documentation as per ICH guidelines

### Leading Technology

- Machine filled PUF insulation to eliminate void pockets
- Unique design of thermal barrier for better energy efficiency
- Hermetically sealed Compressor with CFC free refrigerant
- Microprocessor controller with LED display
- Sensor failure alarm

### User Friendly

- Digital LED display of Temperature with set, process value & audio visual alarm
- Chamber calibration port on side
- Adjustable trays
- Data logger for 8 Point temperature recording with sensor, printer interface and software (Optional)
- **Also available 4" LCD version with additional features (Details overleaf)**

### Safety

- Alarms for high/low set parameters
- Electrical circuit breaker
- Time delay for compressor switch on
- Overload cut off relay for compressor



Specifications subject to change without notice



# Cold Cabinets


### Additional Features for LCD version:-

- 4 Inch attractive LCD display
- Intelligent Controller helps maintain temperature in case of sensor failure
- Battery Backup for Temperature Controller - 12 V, 7.2 Ah sealed maintenance free, Fully charged battery runs for more than eight hours
- Automatic Calibration of set parameters
- Self-Diagnosis for errors
- Histogram format of 24 hours temperature recording
- Power failure and resumption recorded with date and time
- Settable High / low alarm points with date and time
- Memory for storage of upto 1000 records
- Centronic interface to record Temperature, Date, & Time by attaching Dot Matrix printer with adjustable print interval
- Alarm on equipment / security gate
- PC communication with RS-485 and software complying to 21 CFR part 11 as per USFDA guidelines

### Features of Software complying to 21 CFR part 11

- Multiple level alpha numerical password with password ageing
- Electronic signature and menu entered comment
- Secured audit trail report
- Alarm report with mention of alarm condition
- Mean Kinetic Temperature able to be calculated for any days & alarm deviation report
- Reports in graphical and tabular form
- Data Stored in PC server with Lan connectivity and can be monitored on any PC with password authentication
- Multi chamber data acquisition on single software

**GMP versions are available only with LCD display with its built-in features and software**



Technical Data					
	CC - 6 Plus	CC - 10 Plus	CC - 12 Plus	CC - 16 Plus	CC - 19 Plus
Internal Volume (Litres)	200	280	370	450	540
Number of tray	2	3	4	5	6
Internal Dimensions W x D x H (mm)	660x655x450	660x655x650	660x655x850	660x655x1050	660x655x1250
External Dimensions W x D x H (mm)	800x1095x1020	800x1095x1220	800x1095x1420	800x1095x1620	800x1095x1820
Temperature Range & Accuracy	2°C to 12°C, ± 0.5°C				
Temperature control	Microprocessor with PT-100 sensor				
Display	1" - 7 Segment, Big Size LED				
Power Failure Alarm	Audio Visual Alarm				
Door Open Alarm	Audio Alarm in case door open for over one minute				
Temperature Variation Alarm	Set Temperature ± 2°C, Audio Visual Alarm				
Illumination	8 Watts Fluorescent Lamp				
Internal Body Material	Stainless Steel - 304 grade (Standard Models), Stainless Steel - 316 grade (GMP Models)				
External Body Material	Powder Coated CRCA Steel (Standard Models), Stainless Steel - 304 grade (GMP Models)				
Insulation	70 mm minimum for Body & 80 mm for Door, CFC free polyurethane foam				
Noise Level	Less Than 65 db(A)				
Recommended Voltage Stabilizer	VS-02	VS-02	VS-02	VS-03	VS-03
Electrical	220-240 volts, 50Hz, Single Phase				

