Haemoglobin Meter Haemoglobin Meter

1315



- Direct Display in Hb Units
- 1ml Sample Volume
- Highly Accurate and Easy to Operate
- Storage of Factor in Memory

Microprocessor Haemoglobin Meter Model 1315 is used to determine the haemoglobin concentration in the blood sample.

The measurement of haemoglobin concentration is carried out at wavelength of 546nm. Using state-of-art LED technology, the green light produced is passed through the sample and measured by sensitive photodiode. The measurements are made using cyanmethemoglobin method used throughout the world.

Haemoglobin is an iron-containing protien found in red blood cells. It enables the red cells to carry oxygen from the lungs to the rest of the body and carry carbon dioxide back. The haemoglobin level indicates the blood's oxygen-carrying capacity and can play a major role in the early diagnosis of many illness such as thalassemia, sickle cell anemia, leukemia, malaria and hook worm etc.

ENVIRONMENTAL AND SCIENTIFIC INSTRUMENTS CO AN ISO 9001: 2000 CERTIFIED CO.



μp Haemoglobin Meter

MEASURING METHOD Cyanmethemoglobin MEASURING RANGE 0-30 gm/dl of Hb 1:251 SAMPLE VOLUME 1 ml DISPLAY 3 Digit 7 Segment Red LED Display WAVELENGTH Soft Touch 3 Keys ZERO SETTING Automatic CALIBRATION Automatic DETECTOR Highly Sensitive Silicon Photo Diode POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH) ACCESSORIES Glass Test Tubes, Dust Cover, Operation Manual	Technical Data	
DILUTION RATIO 1: 251 SAMPLE VOLUME 1 ml DISPLAY 3 Digit 7 Segment Red LED Display WAVELENGTH 546 nm KEYBOARD Soft Touch 3 Keys ZERO SETTING Automatic CALIBRATION Automatic DETECTOR Highly Sensitive Silicon Photo Diode POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH)	MEASURING METHOD	Cyanmethemoglobin
SAMPLE VOLUME DISPLAY 3 Digit 7 Segment Red LED Display WAVELENGTH 546 nm KEYBOARD Soft Touch 3 Keys ZERO SETTING Automatic CALIBRATION Automatic DETECTOR Highly Sensitive Silicon Photo Diode POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH)	MEASURING RANGE	0-30 gm/dl of Hb
DISPLAY 3 Digit 7 Segment Red LED Display WAVELENGTH 546 nm KEYBOARD Soft Touch 3 Keys ZERO SETTING Automatic CALIBRATION Automatic Highly Sensitive Silicon Photo Diode POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH)	DILUTION RATIO	1 : 251
WAVELENGTH Soft Touch 3 Keys ZERO SETTING Automatic CALIBRATION Automatic DETECTOR Highly Sensitive Silicon Photo Diode POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH)	SAMPLE VOLUME	1 ml
KEYBOARDSoft Touch 3 KeysZERO SETTINGAutomaticCALIBRATIONAutomaticDETECTORHighly Sensitive Silicon Photo DiodePOWER SOURCE230 ± 10% VAC, 50HzDIMENSIONS195 X 235 X 105 (LXBXH)	DISPLAY	3 Digit 7 Segment Red LED Display
ZERO SETTING Automatic Automatic DETECTOR Highly Sensitive Silicon Photo Diode POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH)	WAVELENGTH	546 nm
CALIBRATIONAutomaticDETECTORHighly Sensitive Silicon Photo DiodePOWER SOURCE $230 \pm 10\%$ VAC, 50 HzDIMENSIONS $195 \times 235 \times 105$ (LXBXH)	KEYBOARD	Soft Touch 3 Keys
DETECTOR Highly Sensitive Silicon Photo Diode POWER SOURCE $230 \pm 10\%$ VAC, 50 Hz DIMENSIONS $195 \times 235 \times 105$ (LXBXH)	ZERO SETTING	Automatic
POWER SOURCE 230 ± 10% VAC, 50Hz DIMENSIONS 195 X 235 X 105 (LXBXH)	CALIBRATION	Automatic
DIMENSIONS 195 X 235 X 105 (LXBXH)	DETECTOR	Highly Sensitive Silicon Photo Diode
	POWER SOURCE	230 ± 10% VAC, 50Hz
ACCESSORIES Glass Test Tubes, Dust Cover, Operation Manual	DIMENSIONS	195 X 235 X 105 (LXBXH)
	ACCESSORIES	Glass Test Tubes, Dust Cover, Operation Manual
WEIGHT 2.5 Kg. (Approx.)	WEIGHT	2.5 Kg. (Approx.)

Specifications are subject to change due to continuous improvements

Product Range

Semi Auto Analyser, Single Beam and double Beam UV/VIS Spectrophotometer, Flame Photometers, Haemoglobin Meter, Digital pH, Meter, Digital Photo Fluorometer, Digital Conductivity Meter, Digital Photo Colorimeter, Turbidity Meter, Auto KF Titrimeter, Digital DO Meter, Digital Conductivity Meter, Digital TDS Meter, Temperature Indicator, Digital Telethermometer, Water & Soil Analysis Kit, Digital Salinity Meter, Digital Colony Counter, Portable pH Meter, Portable Conductivity Meter, Portable TDS Meter, Portable DO Meter, Digital Tablet Disintegration Apparatus, Digital Friability Test Apparatus Tablet Dissolution Test Apparatus, Melting Point Apparatus, Student Microscope, Binocular microscope, Medical Microscope, Co-Axial Microscope.

ENVIRONMENTAL
AND SCIENTIFIC
INSTRUMENTS CO.
AN ISO 9001: 2000 CERTIFIED CO.

